
## GlobeSurfer® III



## 3G+ Broadband Access Data and Voice wireless gateway

- > High-speed: Download 7.2 Mbps, Upload 5.76 Mbps
- > Powerful Wi-Fi Network router
- > Easy to use: Intuitive 2-button control
- >Unique Notifier software displays alerts and status information across the wireless network
- > Built-in security and firewall functionality
- > Smart design: Desktop or wall-mounted





## GlobeSurfer® III

Packed with new and unique features, the GlobeSurfer® III pushes the boundaries of conventional gateway routers.

Using a Qualcomm 7225 chipset, this clever device offers HSUPA at 5.76 Mbps, as well as AWS support – making it a forerunner in the bandwidth market.

Naturally, it comes with full telephone functionality, including composing, reading and managing SMS text messages.

Hard drives and printers can be connected via the integrated USB port. This means users have access to a central storage system, allowing them to back-up critical files, or share files across the LAN. Multimedia files such as MP3s or AVIs can be streamed across the network. A printer can be conveniently located and used by all connected PCs.

The GlobeSurfer® III is easy to use too, with just two buttons and a clear, colour display screen. The browser has been sub-divided into two sections, so users who only require basic features such as SMS, Telephone, Quick Set-Up and Security can perform all these tasks without having to navigate through more complex functions within the advanced section.



Specifications	
Wireless WAN Interface UMTS/HSDPA/HSUPA WCDMA 850/900/AWS/1900/2100 Mhz 3GPP FDD Compliant 5.7 / 7.2 Mbps peak rate UE Power Class 3 (+24 dBm) Receiver Diversity on all bands, high and low EDGE > 850/900/1900/2100 MHz > GSM Power Class 4 (2W) for 850/900 bands > GSM Power Class 1 (1W) for 1900/2100 bands > EDGE Class E2 (+27 dBm in 850/900 bands, +26 dBm in 1900/2100 bands > GPRS/EDGE Multislot Class 10 (4 slots Rx, 2 slots Tx, 5 max active) > GPRS / EDGE Class B Type 1 MT Voice Support (UMTS and GSM) > RJ11 POTS port > AMR, FR, HFR voice codecs > Caller ID presentation on colour display > DTMF signal pass through Notifier Software > Sends event based information to the client PC/Mac	LAN Interfaces  IEEE 802.11b/g WLAN Access Point  > WEP, WPA, WPA2  > 802.11b/g  > MAC address blocking  > Possible to disable WLAN radio>  USB  > Support for external HDDs or USB printers  Ethernet  > 10/1000 Mbps Auto MDX  LAN services  > DHCP server and proxy  > DNS server and proxy  VPN functionality  > VPN pass through  > PPTP and IPSec client and server  > L2TP client  Firewall and Gateway features  > Advanced NAT  > MAC address filtering  > Demilitarised Zone (DMZ)  > DoS and intrusion protection  > Stateful Packet Inspection  > Configurable security policies  > Application Level Gateway (ALG) modules  > Event logging  > DHCP and DNS server and proxy  > Time
Additional specifications	
Colour LCD showing device status, network information, signal strength, new SMS indicator, missed calls, current time and animations during boot/shutdown     External antenna connector     Remote management through SNMP v1, 2 & 3 and Command Line Interface (CLI)     Intuitive wizard-driven configuration     External 110-240V power adapter	> Dimensions: 150mm x 100mm x 32mm > Weight: 255 grams plus power adapter > Desktop Form Factor and Wall mountable > Operating environment – for indoor use: 0°C to +45°C, 5 – 95% humidity
Approvals & Certifications	
> All applicable regulatory approvals, Operator and Infrastructure IOT	> Microsoft WHQL certified drivers
Available accessories	

> External antenna







As part of their continual product improvement process, Option reserves the right to alter the specifications for the product detailed here. Copyright ©2008 OPTION. All rights reserved. Option, GlobeSurfer and the Option logo are registered trademarks of Option. All third-party trademarks are the property of their respective owners.

