



698-2700 MHz 6/7 dBi Fiberglass Omni Antenna

TerraWave's 698-2700 MHz 6/7 dBi Fiberglass Omni Antenna is designed to operate in the 698-2700 MHz frequency range. This antenna features a fiberglass exterior and is terminated with one N Jack connector. This antenna is ideal for use in any environment where it must withstand exposure to moisture and dust. Included with the antenna is mounting hardware that allows for wall or mast mount installation. *Every TerraWave antenna is covered by the company's two-year TerraNet warranty program. For questions or to purchase product, contact your Regional Sales Executive at 210-375-8482, 800-851-4965 or sales@terra-wave.com.*


Specifications		
Model	M3060070010006OSS	
Frequency Range	698~960 MHz	1710~2700 MHz
Bandwidth	262 MHz	990 MHz
Gain	6 dBi	7 dBi
Vertical Beamwidth	40°	
Horizontal Beamwidth	20°	
VSWR	≤ 2.0	
Nominal Impedance	50 Ohms	
Polarization	Vertical	
Max Power	50 Watts	
Connector	N Jack	
Mount Style	Wall or Mast Mount	
Dimensions	3" x 26.7" x 3.9"	




E Plane Low Band



E Plane High Band



H Plane Low Band



H Plane High Band

